

PRODUCT DATA SHEET

DUR-O-BOND.

MB8020

Polyester Bonding Compound

CHEMICAL FAMILY:

UNSATURATED POLYESTER RESIN

PRODUCT DESCRIPTION:

- **DUR-O-BOND MB8020** is heavy weight polyester bonding compound engineered for bonding FRP parts and for gel coat back-up and radius / contour forming applications.
- Smooths sharp corners and transitions to reduce air voids.
- Low shrinkage and exotherm reduce print thru and allow higher quality finishes.
- Excellent adhesion and shear strength.
- Tough and resilient remains flexible to prevent cracking.

PRODUCT SPECIFICATIONS:

- Color / Odor: Off white with typical styrene odor
- Weight / Gallon: ~ 12.0 ± .04 lbs
- Viscosity: [Brookfield RVDVII, 5 RPM, Spindle TE]: 200,000 300,000 cps
 MB8020-HV: 250,000 cps +
- VOC: 2.53 #/GL [VOC wt/gl after mixing with MEKP: 0 lbs]
- Shelf Life: 6 months unopened (25°C)

Catalyzation / Gel Times:

Catalyst % by Wt. (MEKP)	Gel Time	Peak Temp.	Gel - Peak Exotherm. Time.
1.5 %	~ 20 min.	~ 180°F	~ 15 min.

Note: The above catalyzation results were obtained using a 100 g sample at 25°C (77°F). Incubator Temperature: 77 °F; MEKP Catalyst = Syrgis MEKP-9 or equivalent.

MEKP Usage Guide	Quart		Single Gallon		5 gallons	
Recommended Amount	Volume (mL)	Weight (g)	Volume (mL)	Weight (g)	Volume (mL)	Weight (g)
1.50 %	18.59	20.41	74.38	81.65	371.89	408.24
	Volume	Weight	Volume	Weight	Volume	Weight
Recommended Amount	(fl.oz)	(oz)	(fl.oz)	(oz)	(fl.oz)	(oz)
1.50 %	0.63	0.72	2.51	2.88	12.57	14.40

DUR-O-BOND®

$\textbf{BETTER} \mathrel{\scriptstyle \odot} \textbf{STRONGER} \mathrel{\scriptstyle \odot} \textbf{FASTER}$

NOTICE: Read all precautionary labels, MSDS guidelines and product warnings before using. The information contained herein is correct to the best of our knowledge and is subject to revision without notice. The data contained in this product bulletin is made without guarantee or representation as to results. Since application variables are a major factor in product performance, this information should serve as a general guide only. We suggest that laboratory testing should be performed prior to the use of any product in the field. Durant makes no warranties, express or implied, and limits any liability for breach of warranty, negligence or otherwise to the purchase price of the material.