

SDS Revision Date: 07/31/2017

## 1. Identification

1.1. Product identifier

Product IdentityDur-O-Bond KF1000Alternate NamesDur-O-Bond KF1000

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended useSee Technical Data Sheet.Application MethodSee Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

**Company Name** Durant Performance Coatings, Inc.

112 Railroad St Revere, MA 02151

**Emergency** 

CHEMTREC (USA) (800) 424-9300 Customer Service: Durant Performance Coatings, Inc. (800) 420-0021

# 2. Hazard(s) identification

#### 2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor.

Acute Tox. 4;H332 Harmful if inhaled.
Skin Irrit. 2;H315 Causes skin irritation.

Eye Irrit. 2;H319 Causes serious eye irritation.

Skin Sens. 1;H317 May cause an allergic skin reaction.

### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Warning

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.



SDS Revision Date: 07/31/2017

#### [Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P235 Keep cool.

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves / eye protection / face protection.

#### [Response]:

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P308+313 IF exposed or concerned: Get medical advice / attention.

P321 Specific treatment (see information on this label).

P331 Do NOT induce vomiting.

P333+313 If skin irritation or a rash occurs: Get medical advice / attention.

P337+313 If eye irritation persists: Get medical advice / attention.

P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P362 Take off contaminated clothing and wash before reuse.

P363 Wash contaminated clothing before reuse.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

## [Storage]:

P403+233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

#### [Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.



SDS Revision Date: 07/31/2017

# 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification		
Calcium carbonate CAS Number: 0001317-65-3	10-20	Not Classified	[1][2]	
Styrene CAS Number: 0000100-42-5	25 - 35	Flam. Liq. 3;H226 Acute Tox. 4;H332 Skin Irrit. 2;H315 Eye Irrit. 2;H319	[1][2]	
Amorphous fumed silica CAS Number: 0112945-52-5	1.0 - 10	Not Classified	[1]	
Cobalt 2-Ethyl Hexanoate CAS Number: 0000136-52-7	0.10 - 1.0	Acute Tox. 4;H302 Skin Irrit. 2;H315 Skin Sens. 1;H317 Aquatic Chronic 2;H411	[1]	

<sup>[1]</sup> Substance classified with a health or environmental hazard.

## 4. First aid measures

#### 4.1. Description of first aid measures

**General** In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

**Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give

artificial respiration. If unconscious place in the recovery position and obtain immediate

medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and

seek medical attention.

**Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a

recognized skin cleanser.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

**Overview** No specific symptom data available.

Possible cancer hazard. Contains an ingredient which may cause cancer based on animal

data (See Section 3 and Section 15 for each ingredient). Risk of cancer depends on

duration and level of exposure. See section 2 for further details.

**Inhalation** Harmful if inhaled.

**Eyes** Causes serious eye irritation.

**Skin** May cause an allergic skin reaction. Causes skin irritation.

<sup>[2]</sup> Substance with a workplace exposure limit.

<sup>\*</sup>The full texts of the phrases are shown in Section 16.



SDS Revision Date: 07/31/2017

## 5. Fire-fighting measures

#### 5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO<sub>2</sub>, powder, water spray.

Do not use: water jet.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: No hazardous decomposition data available.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Keep cool.

Ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust / fume / gas / mist / vapors / spray.

Do not get in eyes, on skin, or on clothing.

#### 5.3. Advice for fire-fighters

None

ERG Guide No. 127

## 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

#### 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

#### 6.3. Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations. (See section 13).

Clean, preferably with a detergent. Do not use solvents.

Do not allow spills to enter drains or watercourses.

If drains, sewers, streams or lakes are contaminated, inform the local water company immediately. In the case of contamination of rivers, streams or lakes the Environmental Protection Agency should also be informed.



SDS Revision Date: 07/31/2017

# 7. Handling and storage

### 7.1. Precautions for safe handling

The requirements of the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations apply if the flashpoint is between 21°C and 32°C.

See section 2 for further details. - [Prevention]:

### 7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Naked flames and smoking should not be permitted in storage areas. It is recommended that fork lift trucks and electrical equipment are protected to the appropriate standard.

Incompatible materials: No data available.

See section 2 for further details. - [Storage]:

## 7.3. Specific end use(s)

No data available.

# 8. Exposure controls and personal protection

#### 8.1. Control parameters

#### **Exposure**

CAS No.	Ingredient	Source	Value
0000100-42-5 Styrene		OSHA	TWA 100 ppm C 200 ppm 600 ppm (5-minute maximum peak in any 3 hours)
		ACGIH	TWA: 50 ppm STEL: 75 ppm 2B
		NIOSH	TWA 50 ppm (215 mg/m3) ST 100 ppm (425 mg/m3)
0000136-52-7 Cobalt 2-Ethyl Hexanoate		OSHA	PEL 0.1 mg/m3
		ACGIH	TLV 0.02 mg/m3
0001317-65-3 Calcium carbonate		OSHA	TWA 15 mg/m3 (total) TWA 5 mg/m3 (resp)
		ACGIH	TWA: 10 mg/m3 Ceiling: 20 mg/m3
		NIOSH	TWA 10 mg/m3 (total) TWA 5 mg/m3 (resp)

### Carcinogen Data

CAS No.	Ingredient	Source	Value
0000100-42-5	Styrene	OSHA Select Carcinogen: No	
		NTP Known: No; Suspected: Yes	
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;

8.2. Exposure controls

**Respiratory** If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.



SDS Revision Date: 07/31/2017

**Eyes** Protective safety glasses recommended

Skin Wear overalls to keep skin contact to a minimum.

**Controls** 

Engineering Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure

limits suitable respiratory protection must be worn.

Other Work Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse. **Practices** 

See section 2 for further details. - [Prevention]:

# 9. Physical and chemical properties

**Appearance Opaque Paste** Odor Pungent Styrene Odor threshold Not Measured Hq No Data Available

Melting point / freezing point Not Measured

Initial boiling point and boiling range 293°F **Flash Point** 88°F

**Evaporation rate (Ether = 1)** Slower than Ether Flammability (solid, gas) Not Applicable

Upper/lower flammability or explosive limits Lower Explosive Limit: Not Measured

**Upper Explosive Limit:** Not Measured

Vapor pressure (Pa) Not Measured **Vapor Density** Heavier than Air

**Specific Gravity** .74

Solubility in Water Not Measured Partition coefficient n-octanol/water (Log Kow) Not Measured **Auto-ignition temperature** Not Measured **Decomposition temperature** Not Measured Viscosity (cSt) Not Measured **VOC Content** 251 VOC g/L

9.2. Other information

No other relevant information.

# 10. Stability and reactivity



SDS Revision Date: 07/31/2017

## 10.1. Reactivity

Hazardous Polymerization will not occur.

## 10.2. Chemical stability

Stable under normal circumstances.

#### 10.3. Possibility of hazardous reactions

No data available.

#### 10.4. Conditions to avoid

No data available.

### 10.5. Incompatible materials

No data available.

## 10.6. Hazardous decomposition products

No hazardous decomposition data available.

# 11. Toxicological information

## **Acute toxicity**

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Styrene - (100-42-5)	2,650.00, Rat - Category: 5	No data available	12.00, Rat - Category: 4	No data available	No data available
Amorphous fumed silica - (112945-52-5)	3,160.00, Rat - Category: 5	No data available	No data available	No data available	No data available
Cobalt 2-Ethyl Hexanoate - (136-52-7)	1,220.00, Rabbit - Category: 4	5,000.00, Rat - Category: 5	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)	4	Harmful if inhaled.
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization		Not Applicable
Skin sensitization	1	May cause an allergic skin reaction.
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable



SDS Revision Date: 07/31/2017

STOT-single exposure	 Not Applicable
STOT-repeated exposure	 Not Applicable
Aspiration hazard	 Not Applicable

# 12. Ecological information

## 12.1. Toxicity

Toxic to aquatic life

#### **Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish,	48 hr EC50 crustacea,	ErC50 algae,	
	mg/l	mg/l	mg/l	
Styrene - (100-42-5)	4.08, Pimephales promelas	4.70, Daphnia magna	0.00 (96 hr),	

## 12.2. Persistence and degradability

There is no data available on the preparation itself.

### 12.3. Bioaccumulative potential

Not Measured

### 12.4. Mobility in soil

No data available.

## 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

#### 12.6. Other adverse effects

No data available.

# 13. Disposal considerations

#### 13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

# 14. Transport information

DOT (Domestic Surface IMO / IMDG (Ocean ICAO/IATA Transportation) Transportation)

**14.1. UN number** UN1866 UN1866 UN1866

**14.2. UN proper shipping** UN1866, Resin solution, Resin solution, flammable Resin solution,

Page 8 of 10



SDS Revision Date: 07/31/2017

name flammable, 3, III flammable

**14.3. Transport hazard DOT Hazard Class:** 3 **IMDG:** Not Applicable **Air Class:** Not Applicable

class(es) Sub Class: Not Applicable

14.4. Packing group III III III

14.5. Environmental hazards

IMDG Marine Pollutant: No

14.6. Special precautions for user

No further information

# 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected

regulations are represented.

**Toxic Substance** All components of this material are either listed or exempt from listing on the TSCA

Control Act (TSCA) Inventory.

WHMIS Classification B2 D2A

US EPA Tier II Hazards Fire: Yes

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): Yes Delayed (Chronic): Yes

### EPCRA 311/312 Chemicals and RQs (lbs):

Styrene (1,000.00)

#### **EPCRA 302 Extremely Hazardous:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### **EPCRA 313 Toxic Chemicals:**

Styrene

Cobalt 2-Ethyl Hexanoate

## Proposition 65 - Carcinogens (>0.0%):

Benzene

### Proposition 65 - Developmental Toxins (>0.0%):

Benzene

Toluene

### **Proposition 65 - Female Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.



SDS Revision Date: 07/31/2017

Proposition 65 - Male Repro Toxins (>0.0%):

Benzene

New Jersey RTK Substances (>1%):

Calcium carbonate

Styrene

Pennsylvania RTK Substances (>1%):

Calcium carbonate

Styrene

HMIS RATING: Health: 3 Flammability: 2 Reactivity: 0 Protective Equip: G

## 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H331 Toxic if inhaled.

H411 Toxic to aquatic life with long lasting effects.

# This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

This Safety Data Sheet was prepared using information provided by/obtained from the Durant Performance Coatings, Inc. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to the product. Durant Performance Coatings, Inc. expressly disclaims all expressed or implied warranty and assumes no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other processes as to the accuracy of and/or sufficiency of such information. This Safety Data Sheet may not be changed or altered in any way without the expressed knowledge and permission of Durant Performance Coatings, Inc.

**End of Document**